

## METHOD OF FORMING GATE INSULATING FILM FOR SEMICONDUCTOR ELEMENT

Patent number:

JP2001210834

**Publication date:** 

2001-08-03

Inventor:

JON-HAKU BAEKU

**Applicant:** 

HYUNDAI ELECTRONICS IND CO

LTD

**Classification:** 

- international:

H01L29/786; H01L21/336;

H01L21/316; H01L21/8234;

H01L27/088

- european:

Application number: JP20000368359 20001204

Priority number(s):

## Abstract of JP2001210834

PROBLEM TO BE SOLVED: To provide a method of forming gate insulating film for semiconductor element by which the thicknesses of gate insulating films can be adjusted in accordance with the characteristics of each element in a semiconductor substrate and, at the same time, the substrate can be prevented from being damaged. SOLUTION: In this method, a first gate insulating film 204 is formed on a semiconductor substrate 200 and a silicon nitride film 205 and a photoresist film are successively formed on the insulating film 204. Then a photoresist pattern 206 is formed by leaving the photoresist on a low-voltage element forming area 202 in a photolithography step. In addition, a silicon nitride film pattern 205a is formed by using the photoresist pattern 206 as a mask and the pattern 206 is removed. Finally, a second gate insulating film 207 is formed only on a high-voltage element forming area 203 by using the silicon nitride film pattern 205a as an oxidation preventing mask pattern and the pattern 205a is removed.

Data supplied from the esp@cenet database - Patent Abstracts of Japan